

FORME ACIER pour MINGORI et VIRAX									
∅ intérieur (Pouces)	∅ Intérieur / Extérieur (mm)	∅ intérieur (DN)	∅ Extérieur (mm)	Rayon de courbure fibre neutre (R) en mm	VIRAX	OB30	OB40	OB50	Code
1/8	5/10	DN 6	10,2mm						
1/4	8/13	DN 8	13,5mm						
3/8"	12/17	DN 10	17,2mm	46,5mm		X	X		502C
				40mm	X	X	X		502W-01
1/2"	15/21	DN 15	21,3mm	55,5mm		X	X		502D
				50mm	X	X	X		502W-03
3/4"	20/27	DN 20	26,9mm	71mm		X	X		502E
				65mm	X	X	X		502W-04
1"	26/34	DN 25	33,7mm	94mm		X	X		502F
				100mm	X	X	X		502W-05
1 1/4"	33/42	DN 32	42,4mm	130mm		X	X		502G
				132mm	X	X	X		502W-07
1 1/2"	40/49	DN 40	48,3mm	163mm		X	X		502H
				160mm	X	X	X		502W-02
2"	50/60	DN 50	60,3mm	220mm		X	X		502I
				210mm	X	X	X		502W-06
2 1/2"	60/76	DN 60	76,1mm	340mm			X		502J
3"	80/90	DN 80	88,9mm	530mm			X	X	502K
3 1/2"	90/102	DN 90	101,6mm	830mm				X	502L
4"	102/114	DN 100	114,3mm	1060mm				X	502M

FORME ALUMINIUM pour MINGORI et VIRAX											
∅ intérieur (Pouces)	∅ Intérieur / Extérieur (mm)	∅ intérieur (DN)	∅ Extérieur (mm)	Rayon de courbure fibre neutre (R) en mm	VIRAX	OB30	OB40	OB50	Code		
3/4"	20/27	DN 20	30mm	165mm		X	X		502Q		
1"	26/34	DN 25	35mm	200mm		X	X		502R		
1 1/4"	33/42	DN 32	40mm	220mm		X	X		502S		
			45mm	270mm		X	X		502T		
1 1/2"	40/49	DN 40	50mm	295mm		X	X		502U		
2"	50/60	DN 50	mm	390mm		X	X		502V		
Diamètre embout piston					VIRAX		40 mm				
							OB30		36 mm		
							OB40		36 mm		
							OB50		61 mm		

8 rue de la commune de Paris
 ZI BP 33
 77370 Nangis
 Tél : 01 64 60 50 50
 Fax : 01 64 08 17 98
 E-mail : sdel_materiel@sdel.fr

68 rue Edith Cavell
 94400 Vitry Sur Seine
 Tel : 01 49 60 15 10
 Fax : 01 49 60 15 11

Siège social : SDEL IDF INDUSTRIE
 5-7 Rue du général Leclerc – BP 56
 77722 MORMANT Cedex
 RCS 479 405 102 - Siret 479 102 00035 - TVA intracom FR 04 479 405 102 - Code APE 7732 Z